

Specifications — VC 50

Control — peripheral equipment

Control port..... (1) 3.5 mm direct insertion captive screw connector, 3 pole
Pin configuration..... 1 = +10 VDC, 2 = volume (variable voltage), 3 = GND
Volume control voltage range 0 V (mute) to 10 V (maximum volume)

General

Power Not powered
Temperature/humidity..... Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing
Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling Convection, no vents
Mounting
Furniture or wall mount... Yes, in a one gang opening
Enclosure type High-impact plastic
Enclosure dimensions
Faceplate..... 4.5" H x 2.75" W x 0.13" D
(11.4 cm H x 7.0 cm W x 0.3 cm D) (1 gang)
Device/circuit board..... 1.3" H x 1.4" W x 1" D
(3.3 cm H x 3.5 cm W x 2.5 cm D)
(Depth excludes knob.)
Product weight 0.5 lb (0.3 kg)
Shipping weight 1 lb (1 kg)
Vibration..... ISTA 1A in carton (International Safe Transit Association)
Regulatory compliance
Safety..... CE, c-UL, UL
EMI/EMC CE, C-tick, FCC Class A, ICES, VCCI
Warranty 3 years parts and labor

NOTE All nominal levels are at ±10%.

NOTE Specifications are subject to change without notice.

7.6-120409-D5-111612